

CS-H6c Pro

EZVIZ CS-H6c Pro 2MP 4MM IR 10m Wi-Fi 2 way audio MicroSD up to 512 GB Indoor Mini PT Kamera

Model	CS-H6c Pro
Brend	Ezviz
Meqapixel	2 MP
Səs	İkiterəfli səs
Micro SD	512Gb
Gecə görmə məsafəsi	10m
Internet	Wifi
İş mühiti	Indoor



Specification

Model	CS-H6c-R105-1L2WF
Image sensor	F1.6@1/3" Progressive Scan CMOS
Shutter Speed	Self-adaptive shutter
Lens	4mm, view angle: 90°(Diagonal), 80° (Horizontal), 43°(Vertical)
Lens Mount	M12
Day & Night	IR-cut filter with auto-switching
DNR	3D DNR
WDR	Digital WDR
Video Compression	H.264/H.265
Video Bit Rate	Adaptive bit rate.
Max. Resolution	1920 × 1080
Frame Rate	Max:25fps; Self-Adaptive during network transmission
Smart Alarm	Motion detection, Human Detection, Human Tracking, Big Noise Detection, Auto patrol
Wi-Fi Pairing	AP pairing
Protocol	EZVIZ cloud proprietary protocol
Interface Protocol	EZVIZ cloud proprietary protocol
Storage	Micro SD card slot (Max. 512G)
Power	TYPE-C
Wired Network	RJ45 X 1 (10M/100M self-adaptive Ethernet port)
Standard	IEEE802.11b, 802.11g, 802.11n
Frequency Range	2.4 GHz ~ 2.4835 GHz
Channel Bandwidth	Supports 20MHz
Security	WPA/WPA2, WPA-PSK/WPA2-PSK
Transmission Rate	11b: 11Mbps, 11g :54Mbps, 11n :72Mbps
Output Power(EIRP)	19 dBm

Antenna Gain	1.9 dBi
Operating Conditions	-10°C to 45°C (14°F to 113 °F), Humidity 95% or less (non-condensing)
Power Supply	DC 5V/2A
Power Consumption	5W max
IR Range	MAX. 10 meters(32.81ft)
Dimensions	88mm x 88.2 mm x 119mm (3.46" x 3.47" x 4.69")
Packaging Dimensions	103mm x 103mm x 168mm (4.06" x 4.06" x 6.61")
Bare Weight	218g(0.48lb)
In the box	- Camera
	- Power Adapter
	- Power Cable
	- Drill Template
	- Mounting Plate
	- EZVIZ Screw Kit
	- Regulatory Information
	- Quick Start Guide
Certifications	CE / UL / WEEE / REACH / RoHS / UKCA